

The N-TRON® 308FX2-N, an unmanaged Industrial Ethernet switch, is designed for use in industrial data acquisition, control, and Ethernet I/O applications. The rugged DIN-RAIL enclosure protects the switch from harsh environmental conditions, enabling flawless performance in extreme settings.

PRODUCT FEATURES

- Compact Size
- Full IEEE 802.3 and 1613 Compliance
- NEMA TS1/TS2 Compliance
- Extended Environmental Specifications
- Six 10/100 BaseTX RJ-45 Ports
- Two 100BaseFX Ports, ST (shown) or SC
- Supports Full/Half Duplex Operation
- LED Link/Activity Status Indication
- Store-and-Forward Technology
- Auto Senses Speed and Flow Control
- MDIX Auto Cable Sensing (RJ-45)
- Up to 2.6 Gb/s Maximum Throughput
- Rugged Industrial DIN-Rail Enclosure
- Redundant Power Inputs (10-30 VDC)
- N-View™ OPC Switch Monitoring Option
- Bi-Color Status LEDs For Link, Speed, Activity & Duplex
- Port Control

PRODUCT OVERVIEW

The 308FX2-N switch is designed to meet and exceed the most demanding industrial communication requirements while providing high throughput and minimum downtime.

The 308FX2-N provides six RJ-45 auto sensing 10/100BaseTX ports. All ports are full/half duplex capable, using leading-edge Ethernet switching technology. The 308FX2-N auto-negotiates the speed and flow control capabilities of the TX copper port connection and configures itself automatically. The fiber optic ports support full 200Mb/s communications via 100BaseFX. Bi-color LEDs are provided to display the link status, speed and activity of each port as well as power on/off status.

The 308FX2-N is auto sensing, so there is no need to make extensive wiring changes if upgrades are made to host computers, plant systems, or Ethernet I/O modules. The switching fabric simply scales up or down automatically to match network environments. The device supports up to 4,000 MAC addresses, enabling these products to support extremely sophisticated and complex network architectures.

The 308FX2-N is an ideal candidate for upgrading existing hubs and repeaters to increase bandwidth and determinism by virtually eliminating network collisions. The product provides a cost-effective solution while maintaining the plug & play simplicity of an unmanaged hub.



The 308FX2-N simplifies plant wiring by eliminating the need to bring data acquisition and control connections back to a climate controlled environment. The switch has extended operating specifications to meet the harsh needs of the industrial environment, including extended temperature rating, extended shock and vibration specs, redundant power inputs, and a high MTBF (greater than 2M hours).

For cost savings and convenience, the 308FX2-N can be DIN-RAIL mounted alongside Ethernet I/O or other Industrial Equipment. It can also be panel mounted.

To increase reliability, the 308FX2-N contains redundant power inputs. LED's are provided to display power on/off status as well as the link status and activity of each port.

N-VIEW OPC PORT MONITORING (With -N Option Only)

The N-TRON N-View OLE for Process Control (OPC) Server Software can be combined with popular HMI software packages to add network traffic monitoring, trending and alarming to any application using N-TRON switches configured with the N-View option. N-TRON's N-View OPC Server collects 41 different traffic variables per port and five system level variables per switch. This information can provide a complete overview of the network load, service quality, and packet traffic. OPC client software can use N-View OPC Server data to resolve network problems quickly and improve system reliability.

308FX2-N Specifications

Switch Properties

| | |
|--------------------------|-----------------|
| Number of MAC Addresses: | 4,000 |
| Latency (typical): | 2.1 μ s |
| Backplane Speed: | 2.6Gb/s |
| Switching Method: | Store & Forward |

Case Dimensions

| | |
|-----------|-----------------|
| Height: | 5.9" (15cm) |
| Width: | 2.3" (5.8cm) |
| Depth: | 3.8" (9.7cm) |
| Weight: | 1.6 lbs (0.8kg) |
| Din-Rail: | 35mm |

Electrical

| | |
|--------------------------|------------------|
| Redundant Input Voltage: | 10-30 VDC |
| Input Current: | 380 mA@24V |
| Inrush: | 8.5Amp/0.2ms@24V |
| BTU/hr: | 31.1@24V |

Environmental

| | |
|-----------------------------|--------------------------------|
| Operating and Storage Temp: | -40°C to 85°C |
| Operating Humidity: | 10% to 95% (Non Condensing) |
| Operating Altitude: | 0 to 10,000 ft. |

Shock and Vibration (bulkhead mounting)

| | |
|--------------------|------------------------|
| Shock: | 200g@10ms |
| Vibration/Seismic: | 50g, 5-200Hz, Triaxial |

Reliability

| | |
|-------|------------------|
| MTBF: | >2 Million Hours |
|-------|------------------|

Network Media

| | |
|-------------|---------------------|
| 10BaseT: | >Cat3 Cable |
| 100BaseTX: | >Cat5 Cable |
| 100BaseFX | |
| Multimode: | 50-62.5/125 μ m |
| Singlemode: | 7-10/125 μ m |

Fiber Transceiver Characteristics

| Fiber Length | 2km* | 15km** | 40km** | 80km** |
|--------------------|--------|--------|--------|--------|
| TX Power Min | -19dBm | -15dBm | -5dBm | -5dBm |
| RX Sensitivity Max | -31dBm | -31dBm | -34dBm | -34dBm |
| Wavelength | 1310nm | 1310nm | 1310nm | 1550nm |

* Multimode Fiber Optic Cable
** Singlemode Fiber Optic Cable

Connectors

| | |
|---------------|-------------------------------|
| 10/100BaseTX: | Six (6) RJ-45 Copper Ports |
| 100BaseFX: | Two (2) SC or ST Duplex Ports |

Serial Configuration Port

| | |
|-----------------|------------|
| Com Parameters: | 9600,n,8,1 |
|-----------------|------------|

Recommended Wiring Clearance

| | |
|--------|---------------|
| Front: | 4" (10.16 cm) |
| Side: | 1" (2.54 cm) |

Regulatory Approvals

FCC (CFR 47, Part 15, Subpart B, Class A and ANSI C63.4)
ICES-003
CE (IEC 60068: 2-1/2/6/30 and IEC 60533-7)
UL/cUL: Class I, Div 2, Groups A, B, C, and D; T4
(ANSI/ISA 12.12.01-2007)
EN 60079-0/15 ATEX
GOST-R Certified, RoHS Compliant

Designed to comply with:

IACS UR E10 (ABS Type-Approval)
IEEE 1613 for Electric Utility Substations
NEMA TS1/TS2 for Traffic Control



PACIFIC PARTS & CONTROLS, INC.

6255 PRESCOTT COURT • CHINO, CA 91710
909-465-1174 • FAX 909-465-1178
www.pacificparts.com

Electrical Supply Distributor

308FX2-N Industrial Ethernet Switch Ordering Information

| | |
|-----------------|---|
| 308FX2-N-XX | Six 10/100BaseTX Ports, Two Multimode 100BaseFX Fiber Optic Ports |
| 308FX2E-N-XX-YY | Six 10/100BaseTX Ports, Two Singlemode 100BaseFX2 Fiber Optic Ports |
| URMK | 19" Universal Rack Mount Kit |
| 900-PM | Panel Mount Kit |
| NTPS-24.1.3 | N-TRON Power Supply (1.3 amp@24VDC) |

Where: N for N-View, and Blank Otherwise
 XX = ST or SC, YY = 15, 40 or 80 for singlemode, blank for multimode

