

The *N-TRON*® 708TX Industrial Ethernet Switch combines outstanding performance and ease of use. It is ideally suited for connecting Ethernet enabled industrial and/or security equipment and is a fully managed switch.

## PRODUCT FEATURES

- Eight 10/100BaseTX RJ-45 Ports
- -40°C to 85°C Operating temperature
- ESD and Surge Protection Diodes on all Ports
- Auto Sensing 10/100BaseTX, Duplex, and MDIX
- Store-and-forward Technology
- Rugged DIN-Rail Enclosure
- Redundant Power Inputs (10-30 VDC)
- Configurable Alarm Contact
- Configurable Bi-Color Fault Status LED

## Fully Managed Features:

- Full SNMP and Web Browser Management
- Detailed Ring Map and Fault Location Charting
- N-Ring™ Technology with ~30ms Healing
- N-View™ OPC Monitoring
- Plug-and-play IGMP Support
- 802.1Q tag VLAN and Port VLAN
- 802.1p QoS and Port QoS
- Trunking
- Mirroring
- 802.1d, 802.1w, 802.1D RSTP
- DHCP

## Management Features

The 708TX offers several management functions that can be easily configured using a Web Browser.

**IGMP Snooping** - Internet Group Management Protocol is a feature that allows the 708TX switch to forward and filter multicast traffic intelligently.

**VLAN** - Virtual Local Area Network allows you to segment the switch in order to create two or more separate local area network domains.

**QoS** - Quality of Service provides prioritization of network traffic in order to provide better network service. The primary goal of QoS is to improve the latency of prioritized Ethernet packets required for ring management, real-time, and other interactive applications.

**Trunking** - Trunking (Link Aggregation) enables multiple physical ports to be linked together and function as one uplink to another *N-TRON* trunking capable switch configured in the same manner, thereby increasing the bandwidth between switches. This configuration can provide increased bandwidth and redundancy to applications requiring high levels of fault tolerant operation.

**Port Mirroring** - This function allows the traffic on one port to be duplicated and sent to a designated mirror port. Port mirroring can be used to monitor Ethernet traffic on the designated source port using the assigned mirror port.



**Rapid Spanning Tree** - This function allows the switch to be configured in a Ring or Mesh topology, and provides support for redundant path communications with high speed (rapid) healing.

## Remote Monitoring Options

For ease of configuration and monitoring, the 708TX offers Web Browser Management and N-View OLE for Process Control (OPC) Server Software. The *N-TRON* N-View Software can be combined with popular HMI software packages to add network traffic monitoring, trending, and alarming to any application using *N-TRON* switches. In addition SNMP and a COM port interface are available for switch link and status monitoring. The Alarm Contact and Status LED can be configured to respond to power failure on power input 1 or input 2, N-Ring Broken, Partial Break High, Partial break Low, or if multiple Ring managers are detected.

## N-Ring Technology

*N-TRON*'s 708TX Ring Manager using *N-TRON*'s N-Ring technology offers expanded ring size capacity, detailed fault diagnostics, and a standard healing time of ~30ms. The 708TX Ring Manager periodically checks the health of the Ring via packets. If the Ring Manager stops receiving these health check packets, it converts the Ring to a linear bus topology within ~30ms. In addition to standard Ring Manager protocol, when using all *N-TRON* fully managed switches in the ring, a detailed ring map and fault location chart will also be provided on the Ring Manager's web browser and OPC Server to identify the health status of the ring. Up to 250 fully managed *N-TRON* switches can participate in N-Ring topologies.

## Industrial Packaging and Specifications

The 708TX is designed to operate in industrial environments. It is housed in a rugged steel DIN-Rail enclosure. It has extended industrial specifications and features to meet or exceed the operating parameters of the connected equipment. These include extended temperature ratings, extended shock and vibrations specs, redundant power inputs, and high MTBF (greater than 2M hours).

## Ease of Use

The 10/100BaseTX ports are auto sensing and auto configuring. Each copper port is automatically negotiated for maximum speed and performance by default, but can also be hard coded using the user interface. A high speed processor allows wire speed capability on all 100BaseTX ports simultaneously.

## 708TX Industrial Ethernet Switch Ordering Information

708TX                      Eight 10/100BaseTX Ports  
NTPS-24-1.3              N-TRON Power Supply - (1.3 Amp @ 24VDC)

## Specifications

### Switch Properties

Number of MAC Addresses: 8000  
Aging Time: Programmable  
Latency Typical: 2.9  $\mu$ s  
Switching Method: Store-and-Forward

### Physical

Height: 2.26" (5.74cm)  
Width: 6.37" (16.18cm)  
Depth (incl. DIN rail mount): 4.30" (10.92cm)  
Weight (max): 1.60 lbs (0.75kg)  
DIN-Rail Mount: 35mm

### Electrical

Redundant Input Voltage: 10-30 VDC  
Input Current (max): 250mA max @24VDC  
N-TRON Power Supply: NTPS-24-1.3 (1.3A@24V)

### Environmental

Operating Temperature: -40°C to 85°C  
Storage Temperature: -40°C to 85°C  
Operating Humidity: 5% to 95%  
(Non Condensing)  
Operating Altitude: 0 to 10,000 ft.

### Shock and Vibration (bulkhead mounted)

Shock: 200g @ 10ms  
Vibration/Seismic: 50g, 5-200Hz, Triaxial

### Reliability

MTBF: >2 Million Hours

### Network Media

10BaseT: >Cat3 Cable  
100BaseTX: >Cat5 Cable

### Connectors

10/100BaseTX: Eight (8) RJ-45 Copper Ports


### Recommended Wiring Clearance

Front: 2" (5.08cm)  
Side: 1" (2.54cm)

### Regulatory Approvals

FCC Title 47, Part 15, Subpart B - Class A  
CE: EN61000-6-2, 4, EN55011, EN61000-4-2, 3, 4, 5, 6, 8, 11  
UL Listed ANSI/ISA-12.12.01-2000 (US and Canada)  
Class I, Div 2, Groups A, B, C, D, and T4A  
ICES-003 - Class A, ATEX Zone 2, Category 3G,  
II 3G Ex nC IIC (DEMKO 03 ATEX 0316686U)  
GOST-R Certified, RoHS Compliant, Submitted for  
type approval from ABS for Shipboard Applications  
Designed to comply with:  
IEEE 1613 for Electric Utility Substations,  
and NEMA TS1/ TS2 for Traffic control

### Contact Information



**PACIFIC PARTS & CONTROLS, INC.**

6255 PRESCOTT COURT • CHINO, CA 91710  
909-465-1174 • FAX 909-465-1178  
www.pacificparts.com

Electrical Supply Distributor